

要項表

形式		容量(Ah)	外形図	外形寸法(約mm)				液面線高さ(約mm)		質量(約kg)	電解液量(約リットル)
ベント形	シール形	5時間率		W	L	H(最大)		A	B		
						ベント形	シール形				
AH20S	AH20SE	20	(1)	143	*52	273	337	170	30	2.5	0.8
AH30S	AH30SE	30	(1)	143	*52	273	337	170	30	2.7	0.7
AH40S	AH40SE	40	(1)	143	*52	273	337	170	30	2.8	0.7
AH50S	AH50SE	50	(1)	143	*52	273	337	170	30	3	0.7
AH60S	AH60SE	60	(1)	143	*52	276	337	170	30	3.2	0.6
AH80S	AH80SE	80	(1)	143	76	276	337	170	30	4.3	1.1
AH100S	AH100SE	100	(1)	143	76	276	337	170	30	4.6	1
AH120S	AH120SE	120	(2)	145	100	277	368	170	30	5.8	1
AH150S	AH150SE	150	(2)	145	100	277	368	170	30	6.1	0.9
AH200S	AH200SE	200	(3)	170	120	368	448	240	30	11	2.3
AH250S	AH250SE	250	(3)	170	120	368	448	240	30	11.9	2
AH300S	AH300SE	300	(5)	170	195	368	448	240	30	18.1	3.8
AH350S	AH350SE	350	(5)	170	195	368	448	240	30	19.3	3.6
AH400S	AH400SE	400	(5)	170	195	368	448	240	30	20.5	3.4
AH450S	AH450SE	450	(7)	170	285	373	448	240	30	28.4	6.7
AH500S	AH500SE	500	(7)	170	285	373	448	240	30	29.2	6.5
AH600S	AH600SE	600	(8)	170	390	368	525	240	30	37.2	8.1
AH700S	AH700SE	700	(8)	170	390	368	525	240	30	38.5	7.6
AH800S	AH800SE	800	(8)	170	390	368	525	240	30	40	7.2
AH900S	AH900SE	900	(8)	170	515	373	525	240	30	48	11.3
AH1000S	AH1000SE	1000	(8)	170	515	373	525	240	30	49.5	11
AH1200S	AH1200SE	1200	(8)	170	515	373	525	240	30	59	10.5

*シール形の長さ寸法は52にセル間隔6を加え合計58となります。