

## 要項表

形式		容量(Ah) 1時間率	外形図	外形寸法(約mm)				液面線高さ(約mm)		質量 (約kg)	電解液量 (約リットル)
ベント形	シール形			W	L	H(最大)		A	B		
		ベント形	シール形								
AHH20P	AHH20PE	20	(1)	143	*52	272	332	183	30	3.1	0.7
AHH30P	AHH30PE	30	(1)	143	76	282	332	183	30	4.7	1.3
AHH40P	AHH40PE	40	(1)	143	76	282	332	183	30	5.2	1
AHH50P	AHH50PE	50	(2)	145	100	282	332	183	30	6.9	1.4
AHH60P	AHH60PE	60	(2)	145	100	282	332	183	30	7.2	1.2
AHH80P	AHH80PE	80	(4)	170	120	373	441	245	40	11	2.8
AHH100P	AHH100PE	100	(4)	170	120	373	441	245	40	12	2.4
AHH120P	AHH120PE	120	(6)	170	195	373	441	245	40	17	5.3
AHH150P	AHH150PE	150	(6)	170	195	373	441	245	40	19.5	4.6
AHH200P	AHH200PE	200	(7)	170	195	373	441	245	40	20.7	3.2
AHH250P	AHH250PE	250	(7)	170	285	373	441	245	40	31	6.4
AHH300P	AHH300PE	300	(8)	170	390	373	441	245	40	39	9.4
AHH350P	AHH350PE	350	(8)	170	390	373	441	245	40	42	8.6
AHH400P	AHH400PE	400	(8)	170	515	375	443	245	40	51	13
AHH450P	AHH450PE	450	(8)	170	515	375	443	245	40	55	12

\*シール形の長さ寸法は52にセル間隔5を加え合計57となります。